



The GEMINI WR1060 Cabin stands as the flagship of the WR Series, boasting a length of 10.60 meters. This latest addition builds upon the proven 'go-anywhere' capability of its predecessors, the WR780 and WR880, designed to excel in the toughest conditions. Crafted from advanced composite materials, the WR1060 ensures exceptional hull strength, damage resistance, and corrosion resilience. Its stepped volume hull provides outstanding seakeeping, stability, increased payload capacity, and operational ease.

Equipped with Military/Commercial Grade Hypalon 1670 DTEX Sponsons, including options for Double Skinning and additional armor, it offers superior protection. Safety and comfort are prioritized with a spacious cabin ensuring crew well-being in all conditions. Optional features such as; self-righting system, advanced water ballast system, and shock-mitigating seating further enhance safety. The WR1060's design versatility accommodates various configurations and equipment setups tailored to mission-specific needs.

With its large deck space, excellent sea-keeping abilities, and long-range capability, the WR1060 is ideal for roles in Rescue, Military, Commercial, or Law Enforcement. Compliant with international standards and adaptable for local regulations, it supports single or multipoint lifts for safe launch and recovery, making it suitable for diverse roles.

FEATURES

HULL QUALITY

Constructed from advanced composite materials; providing an exceptionally strong structure, and a damage and corrosion resistant craft.

SUPERIOR SEAKEEPING

GEMINI's stepped volume hull offers outstanding seakeeping, improved stability, and increased payload carrying capability, as well as being forgiving to operate.

MILITARY/COMMERCIAL GRADE SPONSON

Heavy Duty Hypalon 1670 DTEX Sponsons with the option for Double Skinning and extra armouring for additional strength and protection.

ULTIMATE SAFETY

Optional self-righting system, advanced water ballast system, and shock-mitigating seating are available to ensure the crew's safety and comfort in all conditions.

PROVEN

A hull design for superior seakeeping, payload carrying and reduced hull slamming supported by advanced shock mitigation seating ensures personnel remain fully capable throughout mission.

CARIN

Optional features such as a separate forward area with galley, toilet, berths, and ample storage, along with air conditioning, heating, and demister systems for crew comfort.

MISSION SPECIFIC

Flexible platform design which can be adapted to differing configuration, bespoke fit out and equipment fit.

INTEROPERABILITY

Available with single or multipoint lifts designed for safe launch and recovery.

COMPLIANCE

Built to international recognised standard, and can be easily equipped and coded to meet local authority regulatory compliance.

TRANSPORTABILITY

The WR1060 is transportable by road on a flat bed truck, or bespoke road trailer. The WR1060 is also one of the few ribs that can fit in an ISO container for secure and cost effective international shipping, and can be made compatible for air transport.

Gemini WR1060

TECHNICAL SPECIFICATIONS

DIMENSIONS -

•	Length overall	10.60m
•	Internal length	7.40m
•	Beam overall	3.25m
•	Internal beam	1.95m
•	Weight (hull, deck and tubes)	1350kg
•	Recommended max pax	18
•	Max load	2429kg

COMPLIANCE AND CERTIFICATION -

GEMINI RIBs can be supplied with various certificates, such as UKCA/CE, ISO, MCA CODING, MGN280, LLOYDS, WORKBOAT CODE, GREYBOAT CODE, depending on the application.

PERFORMANCE DATA -

Approximate performance data with differing engine horse powers and configurations are available on request.

ENGINE OPTIONS - SINGLE OR TWIN INSTALL

Petrol outboards: Yamaha, Mercury, Suzuki. Diesel outboards: Options Available.

Additional power available subject to manoeuvring and speed testing.

•	ISO recommended hp**	500
•	ISO max hp**	640
•	ISO max engine weight**	725kg
•	Max fuel capacity**	1080L
•	Transom height single	30"
•	Transom height double	25"

SPONSON, HULL AND DECK -

0. 000,022 /12 220			
•	Sponson diameter	600mm	
•	Sponson volume	7.225m ³	
•	Inflation pressure	0.25 BAR	
•	Sponson compartments	7	
•	Hull deadrise	20°	
•	Max displacement	4932ka	

STANDARD EQUIPMENT -

- Hypalon sponson (Military Grade 1670 DTEX)
- 2 x heavy duty shark fin rubbing strakes
- 7 x over pressure release valves
- 2 x stainless steel bow eyes
- Full length grab line
- Internally taped seams
- Anchor rope bow protection
- Aluminium keel protection
- Under deck cable track
- 2 x below deck fuel lockers
- Self-draining deck
- 1 x double action pump

DECK CONFIGURATION -

There are a number of differing configurations available, and general arrangement drawings are available on request. In addition custom configurations are available according to weight and balance.

TRAINING -

The following training courses are available:

- Operator training
- Mechanic training
- Specialist equipment training Specialist role training

Consumable and contingency spares packages are available on request.

CABIN SPECIFICATIONS -

Depending on load conditions and GA

- Waterline length +-9.2m
- Max. draught at standard displacement typically 560mm at midpoint of WL
- Overall height from WL to top of cabin +-2.7m
- Overall height from deck to top of cabin +-2.1m
- Cabin weight (including window, hatches & dashboard) +-600Kg
- Light craft condition mass 3866Kg
- Maximum loaded condition mass 4973Kg.
- Seaglaze weather tight door, windows and hatches
- Sleeping berth
- · Toilet systems

OPTIONAL EQUIPMENT

DECK EQUIPMENT -

- · Choice of consoles configurations
- Choice of jockey or shock mitigation suspension seats
- Strengthened deck for high load areas and mounts
- Extra fuel tanks
- Foam filled hull
- M8 deck utility bolt system
- Towing bollard
- Deck track system
- T-top
- Lifting eyes and lifting strops

A-FRAME OPTIONS -

Choice of A-frame configuration and material.

• Engine protection bar • Radar mast • Self-righting system

SPONSONS -

- Additional rubbing strakes on sponsons (1 or 2 extra)
- Additional rubbing strips on the front for bow protection
- Colour strip between strakes Anti-slip surfaces on sponsons
- Upgrade to DTEX 1670

NAVIGATION & COMMUNICATION SYSTEM OPTIONS -

Command and control systems

- VHF radio (fixed and handheld)
- GPS chartplotter
- Magnetic compass
- Night vision equipment
- Entertainment system
- Radar

• AIS

- Depth sounder
- Intercom

Bespoke system integration and system fit available

SPECIALIST EQUIPMENT FIT

Specialist and client supplied equipment fit and integration is available on request at Berthon Boat Company.

DISCLAIMER: Whilst every attempt has been made by GEMINI to give accurate information, all data provided by GEMINI is intended for guidelines only. Engine size, weight and propeller selection can affect a boat's performance and/or regulatory compliance. Regulations perfaining to maximum passengers, payload and permissible engine power and other rules differ from country to country, it is a customer's own the conditions and the control of th



• 2 x paddles

• 1 x repair kit

Anchor locker

• 7 x inflation valves

3 x transom knees

• Engine motor well

• 2 x towing points

· Non-slip deck





